Tubular Extendible Lock-Out Composite Boom (STELOC, Phase I





Completed Technology Project (2013 - 2013)

Project Introduction

Mass and volume efficient solar arrays are sought by NASA, DoD and commercial space to enable high power missions from 20-30 kW up to 300 kW. Flexible substrate arrays can have higher specific power (W/kg) and specific volume (kW/m3) than conventional arrays. Typical designs for flexible substrate arrays require a stiff boom mechanism to deploy the array and provide the deployed structure. Graphite composite slit-tube booms are thermally stable and can enable next-generation flexible arrays by improving mass, volume, and cost. CTD has developed and demonstrated a 5cm diameter graphite composite slit-tube boom and canister designed for a 23m tether-stiffened solar array. The Stable Tubular Extendible Lock-Out Composite (STELOC) boom proposed here will feature two innovations to the composite slit-tube design that enhance stiffness. Slit-Lock interlocks the edges of the slit and Root-Lock eliminates the open section at the root of the boom when fully deployed. Combined, these innovations enable a 10cm STELOC boom that is much simpler, lighter, and stiffer than a 25cm diameter coilable longeron boom. This Phase I program will demonstrate a full length, 10cm STELOC boom including all innovative features to enhance stiffness. The program will also develop a conceptual design that meets all boom requirements provided by an identified spacecraft prime contractor for their flexible substrate array.

Primary U.S. Work Locations and Key Partners





Tubular Extendible Lock-Out Composite Boom (STELOC

Table of Contents

Project Introduction	1
Primary U.S. Work Locations	
and Key Partners	1
Project Transitions	2
Images	2
Organizational Responsibility	2
Project Management	2
Technology Maturity (TRL)	3
Technology Areas	3
Target Destinations	3



Small Business Innovation Research/Small Business Tech Transfer

Tubular Extendible Lock-Out Composite Boom (STELOC, Phase I



Completed Technology Project (2013 - 2013)

Organizations Performing Work	Role	Туре	Location
Composite Technology Development, Inc.	Lead Organization	Industry	Lafayette, Colorado
Langley Research Center(LaRC)	Supporting Organization	NASA Center	Hampton, Virginia

Primary U.S. Work Locations	
Colorado	Virginia

Project Transitions



May 2013: Project Start



November 2013: Closed out

Closeout Documentation:

• Final Summary Chart(https://techport.nasa.gov/file/137635)

Images



Project Image

Tubular Extendible Lock-Out Composite Boom (STELOC (https://techport.nasa.gov/imag e/132026)

Organizational Responsibility

Responsible Mission Directorate:

Space Technology Mission Directorate (STMD)

Lead Organization:

Composite Technology Development, Inc.

Responsible Program:

Small Business Innovation Research/Small Business Tech Transfer

Project Management

Program Director:

Jason L Kessler

Program Manager:

Carlos Torrez

Principal Investigator:

Robert M Taylor

Co-Investigator:


Robert F Taylor



Tubular Extendible Lock-Out Composite Boom (STELOC, Phase I



Completed Technology Project (2013 - 2013)



Technology Areas

Primary:

- TX12 Materials, Structures, Mechanical Systems, and Manufacturing
 - └ TX12.2 Structures
 - ☐ TX12.2.1 Lightweight Concepts

Target Destinations

The Sun, Earth, The Moon, Mars, Others Inside the Solar System, Outside the Solar System

